

HMI-TPND0U-17SR-X00H

17" HMI Panels with Rugged Stainless Steel Bezels
High-Computing Intel® Core™ i7-4650U Processor

Features and Benefits

- Ruggedness, zero maintenance and fan-less HMI systems
- Field-replaceable units of modular touch displays and IPCs
- Rugged stainless steel bezels with compact aluminum housing
- Intel® Core™ i7-4650U CPU, DDR3L-1600 memory up to 16GB
- RAID 1 storage system with onboard RAID controller-SSD x 2
- Externally accessible dual SSD with tool-free installation
- Externally accessible one PCIe slot allows for easy expansion
- Electrical isolation protection on serial ports and DC power
- High temperature, vibration, shock and EMC resistance
- Supports Windows Embedded 7 or 8 operating systems
- UL listing and CB certificates, RoHS, FCC and CE compliant

Introduction

AIS 17" Premium HMI Touch Panels and Modular Box PCs are equipped with high-performance processing power and speed with 64-bit operating systems, Intel® Core™ i7-4650U Processor, DDR3L-1600 memory up to 16GB, RAID 1 storage, IP66 stainless steel bezels and a rugged fan-less aluminum housing offering the most advanced features and capabilities. AIS touch panel HMI offers users a high degree of flexibility for interfaces and expansions. The ability to simply replace the box PC which houses the engine makes upgrading or expanding this AIS control and monitoring system extremely simple.

Specifications

Display	
Size in inches / resolution in pixels	17" / XGA, 1280 x 1024
Brightness / luminance	350 nits / 350 cd/m ²
MTBF of backlight (at 25°C)	LED-backlight up to 100,000 hours in Eco mode
Touchscreen	Single-touch (resistive analog)
System Hardware	
Processor	Intel® Core™ i7-4650U Processor; 4M Cache up to 3.30 GHz, 15 W maximum TDP
# of cores	2
Memory / # of slots	From 8 GB DDR3L 1600 SDRAM, configurable up to 16 GB / 2 slots
Graphics / video	Intel HD graphics; DirectX 11.1, OpenCL /GL, and 4K videos Quick Sync encoder
RAID	RAID 1 system with onboard RAID controller
Drives	
Mass storage	1 x 180 GB SLC SSD, configurable up to 2 x 180 GB SLC SSD RAID 1
Secondary storage	32GB m-SATA SSD
Optical drives	Connection via USB port

Interface ports	
Ethernet	2 x Ethernet TCP/IP - RJ45
USB	4 x USB 3.0
Serial	COM1: RS232/422/485; COM2: RS232, isolated
Graphic	1 x VGA; 1 x HDMI
Audio	1 x Line-in, 1 x Line-out
General features	
Operating system	Windows Embedded 7 32/64-bit ; Windows Embedded 8
Free expansion slot	1 x PCIe card (x4)
Current supply	24 V DC; 9.6 to 28.8 V, isolated
Bezel / housing	Stainless steel / aluminum
Mounting options	Panel PC: Panel / wall mount; Box PC: Wall / din-rail mount
Packages / bundles	Packages with Wonderware InTouch, ready-to-use HMI software (optional)
Environment / ambient conditions	
Degree of protection / thermal	Front: IP66; Rear: IP20 / Fanless
Electromagnetic compatibility	CE, FCC A, EN 61000-6-4, EN 61000-6-3, CISPR22, RoHS
Vibration during operation	Tested according to DIN IEC 60068-2-6: 10 - 58 Hz: 0.075 mm
Shock during operation	Tested according to DIN IEC 60068-2-27: 15 gn for 11 ms
Ambient temperature	0...50°C (32...122°F)
Relative humidity	5 to 95% non-condensing
Certifications / regulations	UL/cUL/IEC 61010-1, UL/cUL/IEC 62368-1, CB reports available for all models
Dimensions	
Operator panel / cut-out (W x H)	408 x 313 mm
Installation dimensions (W x H x D)	418 x 353.7 x 94.6 mm
Product Weight (lb /kg)	
Contractual warranty	
Period	12 months

HMI-TPND0U-17SR-XN0C

Dimensions

Unit: mm

